

Product leaflet

Product	Model designation	Ordering No.
Powered air purifying respirator	SR 500 EX	H06-2012

Product description

The SR 500 EX fan is explosion-proof and specially adapted for use in an explosive atmosphere. The SR 500 EX is included together with filters and head-tops in Sundström fan-assisted respiratory protective devices. The SR 500 EX can be used as an alternative to filter protections in all situations in which the latter are recommended. This applies particularly to situations in which the work is intensive, hot or of long-duration. The fan is equipped with filters and the filtered air is supplied through a breathing hose to the head-top. The latter is then pressurized, which prevents the surrounding pollutants from being admitted.

The SR 500 EX has the following characteristics:

- Explosion proof
- Automatic control of the air flow
- Same control button is used for starting, stopping and selection of operating conditions
- Display with symbols for different operating conditions
- Alarm with audible/visual signals if the air flow is obstructed
- Li-Ion battery
- Operating time of up to 12 hours
- Charging time about 4 hours
- Equipped with two filters/filter combinations
- Can be used together with hoods SR 520, SR 530, SR 561, SR 562, SR 601, SR 602, face shield SR 540 EX, SR 570, helmet with visor SR 575, SR 580 or full face mask SR 200.

Technical specification

	SR 500 EX	EN 12941:1998	EN 12942:1998
Air flow rate	175/225 l/min	≥ 120 l/min	
Li-Ion battery	18 V, 3,0 Ah	-	-
Operating times at 175/225 l/min:			
With particle filter P3	12 h/7 h	≥ 4 h	≥ 4 h
Weight with battery and P3 filter	≈ 1 780 g	≤ 3500 g	≤ 3500 g
Service temperature	-10 to +40 °C, < 90 % RH	-	-
Storage temperature	-20 to +40 °C, < 90 % RH	-	-
Low flow warning level	< 175 l/min	≤ 175 l/min	≤ 175 l/min
Assigned Protection Factor¹ w hoods, SR 540 EX, SR 570, SR 575, SR 580	40 (TH3)	-	-
Assigned Protection Factor¹ w SR 200	40 (TM3)	-	-
Nominal Protection Factor² w hoods, SR 540 EX, SR 570, SR 575, SR 580	500 (TH3)	-	-
Nominal Protection Factor² w SR 200	2000 (TM3)	-	-
Approvals	Directive	Standards	Classification/markings
	PPE Regulation (EU) 2016/425 ATEX 2014/34/EU	EN 12941:1998 + A2:2008, EN 12942:1998 EN IEC 60079-0:2018, EN 60079-11:2012	TH3/TM3 Ex II 2 G Ex ib IIA T3 Gb ³⁾ Ex II 2 G Ex ib IIB T3 Gb ⁴⁾ Ex II 2 D Ex ib IIIC T195°C Db ⁵⁾ Ex ib IIA T3 Gb ³⁾ , Ex ib IIB T3 Gb ⁴⁾ Ex ib IIIC T195°C Db ⁵⁾
	IECEx Scheme	IEC 60079-0:2017, IEC 60079-11:2011	

1) Specified in BS EN 529 and applies generally to all approved fan-assisted respiratory protective devices, regardless of the test results.

2) According to EN 529:2005.

3) SR 500 EX together with shield SR 540 EX, helmet with visor SR 575, SR 580 or full face mask SR 200 with PC visor.

4) SR 500 EX together with hoods SR 520, SR 530, SR 561, SR 562, SR 601, SR 602, shield SR 570 or full face mask SR 200 with glass visor.

5) SR 500 EX together with all Sundström head tops.

Key to EX marking

Ex	ATEX Explosion protection mark.
II	ATEX Equipment group (explosive atmospheres other than mines with fire damp).
2 G	ATEX Equipment category (2 = High level of protection for Zone 1, G = Gas).
2 D	ATEX Equipment category (2 = High level of protection for Zone 21, D = Dust).
Ex	Explosion protected.
ib	Type of protection (Intrinsic safety).
IIA	Gas group (Propane).
IIB	Gas group (Ethylene).
IIIC	Dust material group (zone with conductive dust).
T3	Temperature class, gas (maximum surface temperature +200°C).
T195°C	Temperature class, dust (maximum surface temperature +195°C).
Gb	Equipment Protection Level, gas (high protection).
Db	Equipment Protection Level, dust (high protection).



Sundström Safety AB

Tel: +46 10 484 87 00
Västergatan 4
SE-341 50 Lagan

Sundström
www.srsafety.com



Head-tops, spare parts and accessories

Item No.	Part	Ordering No.
1.	Hood SR 561	H06-5012
2.	Hood SR 562	H06-5112
3.	Hood SR 520 M/L	H06-0212
3.	Hood SR 520 S/M	H06-0312
4.	Hood SR 530	H06-0412
5.	Hood SR 601	H06-5412
6.	Hood SR 602	H06-5512
8.	Face shield SR 540 EX	H06-6012
9.	Face shield SR 570	H06-6512
10.	Full face mask SR 200, PC visor	H01-1212
10.	Full face mask SR 200, glass visor	H01-1312
11.	PU hose SR 550 for SR 200	T01-1216
11.	Rubber hose SR 551 for SR 200	T01-1218
12.	Helmet with visor SR 580	H06-8012
13.	Helmet with visor SR 575	H06-9010
14.	Hose SR 541 for SR 540	R06-0501
15.	O-ring for breathing hose	R06-0202
16.	Flat gasket for hose SR 541	R06-0506
17.	Flow meter SR 356	R03-0346
18.	Belt SR 508 EX	R06-2148
18.	Belt PVC EX	T06-2151
18.	Rubber belt SR 504 EX	T06-2150
19.	Leather belt SR 503 EX	T06-2149
20.	Harness SR 552 EX	T06-2002
21.	Battery SR 502 EX, 3,0 Ah	R06-2070
22.	Battery charger	R06-2081
23.	Fan SR 500 EX, bare	R06-2001
24.	Gasket for fan	R06-0107
25.	Pre-filter holder SR 512 EX	R06-2023
26.	Pre-filter SR 221	H02-0312
27.	Pre-filter holder	R01-0605
28.	Particle filter P3 R, SR 510	H02-1312
29.	Filter adapter SR 511	R06-0105
30.	Particle filter P3 R, SR 710	H02-1512
31.	Gas filter A2, SR 518	H02-7012
32.	Gas filter ABE1, SR 515	H02-7112
33.	Gas filter A1BE2K1, SR 597	H02-7212
34.	Combined filter A1BE2K1-Hg-P3 R, SR 599	H02-7312
35.	Storage bag SR 505	T06-0102
36.	Steel net disc SR 336	T01-2001
37.	Vaseline tube	R06-2016
38.	Plug kit	R06-0703

