

Product
Helmet with visor

Model No.
SR 575

Ordering No.
H06-9010

Product Description

The SR 575 together with the battery-powered SR 500, SR 500 EX or SR 700 fan and approved filters are included in the Sundström fan-assisted respiratory protection device systems. The breathing hose of the helmet with visor is to be connected to the fan, equipped with filters. The pressure generated in the visor prevents particles and other pollutants from entering the breathing zone.

The equipment can be used as an alternative to filter respirators in all situations for which filter respirators are recommended. This applies particularly to work that is hard, warm or of long duration.

The characteristics of the SR 575 helmet with visor are as follows:

Protects the breathing zone and the head • Hinged visor unit • PC visor and visor frame protects from high speed particles 120 m/s at extremes of temperature, liquid splashes and molten metal • The supply air flow keeps the visor demisted • Airflow deflector for optimal comfort • Adjustable head harness • Replaceable breathing air hose • Equipped with an exhalation valve • Optional protective films • Available in one size. • Standard fastener for hearing protection • Optional chemical resistant TAC visor.

The helmet is approved according to EN 397, -30°C, molten metal splash MM, Lateral deformation LD and electrical insulation 440 Vac.

The helmet with visor together with the SR 500 EX fan is approved for use in a potentially explosive atmosphere, with exclusion for protective films as accessories.

- A. SR 575
- B. SR 500
- C. SR 500 EX
- D. SR 700



Sundström Safety AB
Tel: +46 10 484 87 00
Västergatan 4
SE-341 50 Lagan



Sundström
www.srsafety.com

Product
Helmet with visor

Model No.
SR 575

Ordering No.
H06-9010

Technical specification


	SR 575+SR 500/ SR 500 EX/SR 700	EN 12941:1998 + A2:2008
Air flow rate	175-240 l/min (SR 500) 175-225 l/min (SR 500 EX / SR 700)	≥ 120 l/min
Service temperature	-10 – +55°C, < 90 % RH	-
Storage temperature	-20 – +40°C, < 90 % RH	-
Low flow warning level	< 175 l/min	≤ 175 l/min
Weight with breathing hose	≈ 980 g	≤ 1.500 g
Assigned Protection Factor¹	40 (TH3)	-
Nominal Protection Factor²	500 (TH3)	-
Approvals	Directive	Standards
	PPE Regulation (EU) 2016/425	EN 12941:1998 + A2:2008 EN 166, EN 397
	ATEX 2014/34/EU	EN IEC 60079-0:2018, EN 60079-11:2012
	IECEx Scheme	IEC 60079-0:2017, IEC 60079-11:2011
		Classification/markings
		TH3
		 II 2 G Ex ib IIA T3 Gb ³⁾  II 2 D Ex ib IIIC T195°C Db ³⁾ Ex ib IIA T3 Gb ³⁾ Ex ib IIIC T195°C Db ³⁾

1) Specified in BS EN 529 and applies regardless of the test results.

2) According to EN 529:2005.

3) Together with fan SR 500 EX.

Key to EX marking

	ATEX Explosion protection mark.
II	ATEX Equipment group (explosive atmospheres other than mines with fire damp).
2 G	ATEX Equipment category (2 = High level of protection for Zone 1, G = Gas).
2 D	ATEX Equipment category (2 = High level of protection for Zone 21, D = Dust).
Ex	Explosion protected.
ib	Type of protection (Intrinsic safety).
IIA	Gas group (Propane).
IIIC	Dust material group (zone with conductive dust).
T3	Temperature class, gas (maximum surface temperature +200°C).
T195°C	Temperature class, dust (maximum surface temperature +195°C).
Gb	Equipment Protection Level, gas (high protection).
Db	Equipment Protection Level, dust (high protection).



Sundström Safety AB
Tel: +46 10 484 87 00
Västergatan 4
SE-341 50 Lagan

Sundström
www.srsafety.com